



# HX100M 4K HDMI Extender

Commercial-Grade



## One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



### Commercial-Grade

With durable construction and ultra-sleek design, CE Labs extenders are perfect for any project that requires 24/7 performance.



### CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



### 3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

## PRODUCT OVERVIEW

The HX100M is a commercial-grade 1080p HDBaseT HDMI Extender kit. It supports 1080p at 100 meters (328 ft). With an ultra-compact and rugged chassis, the HX100M is ideal for professional environments that require 24/7 performance.

The CE Pro-link™ of HDMI extender kits are the latest generation of reliable HDBaseT extenders for HD/4K/UHD AV signals. The CE PROLink™ series includes HD and UHD models with a variety of powering and extension distance options. Perfect for AV professionals that demand the most cost effective and installation-friendly features.

## FEATURES

Compact Design and rugged steel chassis

Most cost Effective HDBaseT solution

75% lower power consumption

# SPECIFICATIONS

MODEL: HX100M

## FEATURES

- Uses only one Cat5e/6/7 cable
- Transmission range up to 100M by CAT5e/6/6a/7
- 3D ready and 4K2K capable
- Uses HDBaseT technology
- Uncompressed HD video up to 1080p@60Hz@48bits, 4K/30 capable
- HDMI and HDCP Compliance
- RoHs, CE, FCC Compliant
- Cat Cable 5e/6/6a/7 Distance: Min. 10 ft (3M) - Max. 328 ft (100M)
- HDMI Cable Type A Distance: Min. 2 ft - Max. 16 ft
- Max. Data Rate 10.2 Gb/s
- Audio Transmission Full pass-through

## VIDEO

- HDMI 1.4
- HDCP compliance
- Maximum Resolution: 480i/p, 720p, 1080i/P @ 24/50/60Hz, 4K/30
- Max. Distance: 100M @ 4K/30(CAT6)

## AUDIO

- Audio support up to LPCM7.1, Dolby TrueHD, DTS-HD MA
- Audio transmission full pass-through

## POWER

- Wall transformer: 5VDC/ 2A, 2.5 mm connector
- TX Max current: 420mA Power: 0.8-2.5 W
- RX Max current: 950mA Power: 1-5 W

## I/O PORTS

- Transmitter/Receiver HDMI type A
- RJ45 Data Connector
- 2.5mm X 5.5mm female connector Power jack
- LED Indicators: Pwr On = Green, Link = Blue

## RJ45 Define: Video Link (TIA/EIA-568-B)

- |                           |                          |
|---------------------------|--------------------------|
| 1. Orange-White: DATA 0 + | 5. Blue-White: DATA 2 -  |
| 2. Orange: DATA 0 -       | 6. Green: DATA 1 -       |
| 3. Green-White: DATA 1 +  | 7. Brown-White: DATA 3 + |
| 4. Blue: DATA 2 +         | 8. Brown: DATA 3 -       |

## ACCESSORIES

- 2 Power wall adapters
- Set of 4 Plastic Drywall Anchors
- Product Manual

## MISCELLANEOUS

- Transmitter Dims.: (H) 1" x (W) 1.9" x (D) 3.6" | Weight 4.8oz.
- Receiver Dims.: (H) 1" x (W) 1.9" x (D) 3.6" | Weight 4.8oz.
- Operating Temp & Humidity 0-55C, up to 95% Max Rel. Humidity
- Rugged (Industrial) Powder Coated Steel Chassis

WARRANTY: \*3 year warranty, parts and labor.



Learn more about CE Labs at [www.celabs.com](http://www.celabs.com).

United States  
1-800-767-6189  
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

