

UHD860 4K Distribution Amp

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs splitters are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The UHD860 is a 1x8 HDMI splitter with UHD 4K60 resolution capability. CE Labs' commercial–grade HDMI Distribution amplifiers/splitters deliver perfect 4k60 performance and are packed with commercial–grade functionality. Our patented technology is optimized for delivering ultra–high–definition video to large retail TV and point–of–purchase (POP) displays. The UHD860 supports industry–leading 4K UHD technology and is optimized to fully support brilliant HDR10+ at 18 Gigabits, with auto–detect downscaling.

The UHD860 is perfect for retail applications or any demanding video distribution system that require 24/7 operation and true commerical-grade performance.

FEATURES

Superior cascading and ultra 4K60 18Gb distribution.

Auto-detect downscaling.

Patented cable retention system.

SPECIFICATIONS MODEL: UHD860

FEATURES

Ultra-High Definition Distribution Amplifier / Scaler

HDMI 2.0a, HDCP 2.2, and DVI compliant

Compatible with HDR Sources and TVs

1080P downscaler on every output for backwards compatibility

18Gb/S / 600MHz Bandwidth / 4Kx2K @ 60 Hz Full color

4Kx2K @60Hz, 8bit 4:4:4 color with scrambling is supported

Deep Color Compatible on resolutions <600MHz

EDID copy and multi-presets

Cascadable for retail video wall displays (up to 10 times)

Integrated Cable retention bracket (CE labs® patented)

Firmware update port

Hardware Version: Rev. D

1 Input 8 Outputs

VIDEO

HDMI 1.4a, 2.0a

HDCP1.4, or 2.2

HDR Info Frame control is supported

CEC messages from Input to all Outputs

Color Space: Compliant with BT.601, 709, 2020 (non-const.), RGB Full,

RGB Limited

Maximum Pixel Clock: 600MHz

1080P Downscale Available on any output port

720P downscale is not supported

EDID Management – 4 Dip Switches, 8 different settings

HDMI cable 1ft-15ft (5m) for 1080P and 4Kx2K 30 / 60(4:2:0)

HDMI cable 1ft-9ft (3m) for 4Kx2K 60 full color

RESOLUTION

3840x2160, 60Hz, YCbCr4:4:4 - 8Bit only

3840x2160, 60Hz, YCbCr4:2:2 - 8Bit only

3840x2160, 60Hz, YCbCr4:2:0 - 8, 10, or 12Bit

3840x2160, 30Hz, YCbCr4:4:4 - 8, 10, or 12Bit

1920x1080, 60Hz, YCbCr, 4:4:4 - 8, 10, or 12Bit

1280x720, 60Hz, YCbCr, 4:4:4 - 8, 10, 12 or 16 Bit

RGB Full and RGB Limited are also supported

I/O PORTS

9x HDMI type A

2.5mm X 5.5mm female locking connector jack

6 pin DIP switch

1 push buttons

11 LED Red / Green

USB type B connector

AUDIO

Format: LPCM, Dolby, Dolby Digital +, DTS, DTS-HD

Channels: 8

Sample Frequencies: 192, 176, 96, 88, 48, 44.1, 32

Sample Bit: 16, 20, & 24

POWER SUPPLY

Wall transformer: 100-240V 50/60 to 12VDC/1A

Screw on Locking plug 205mm x 5.5mm connector

Efficiency Level VI

ACCESSORIES

1 Power Adapter 100-240 VAC - 12Vdc 1.0Amp 2.5mm

1 Quick Start Guide

9 Tie Wraps

4 Mounting feet

MISCELLANEOUS

Dimensions (H) 1" x (W) 9.5" x (D) 6.9"

Weight 1.85 lbs.

Operating Temp & Humidity 0-55°C, 95% Max Rel. Humidity

Integrated Mounting Brackets

Low Profile Design

Rugged (Industrial) Powder coated steel chassis

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States

1-800-767-6189 sales@celabs.com

