



HX70M 4K HDMI Extender

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs extenders are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The HX70M is a commercial-grade HDBaseT HDMI Extender kit. The HX70M support 1080p at 70 meters (230 ft) and 4K60 at 40 meters (130ft). With an ultra-compact and rugged chassis, the HX70M is ideal for professional environments that require 24/7 performance.

The CE Pro-link™ of HDMI extender kits are the latest generation of reliable HDBaseT extenders for HD/4K/UHD AV signals. The CE Pro-link™ series includes HD and UHD models with a variety of powering and extension distance options. Perfect for AV professionals that demand the most cost effective and installation-friendly features.

FEATURES

Compact Design and rugged steel chassis

Most cost Effective HDBaseT solution

75% lower power consumption

SPECIFICATIONS

MODEL: HX70M

FEATURES

- Uses only one Cat5e/6/7 cable
- 3D ready and 4K2K capable @30Hz
- Settings not required
- Uses HDBaseT lite technology
- Extends HDMI and IR signal over one CAT5e/6/6a/7 cable
- Uncompressed HD video up to 1080p@60Hz@48bits, 4K/30 capable
- HDMI and HDCP Compliance
- Transmission range up to 60M by CAT5e/6,
- Transmission range up to 70M by CAT6a/7
- Built in IR control selectable direction
- RoHs, CE, FCC Compliant
- Cat Cable 5e/6/6a/7UTP/STP Distance: Min. 10'(3M) - Max. 230'(70M)
- HDMI Cable Distance: Min. 2' - Max. 16'
- Max. Data Rate 10.2 Gbps

VIDEO

- HDMI 1.4
- HDCP 1.4 compliance
- Maximum Resolution: 1080P/60HZ@48 bit
 - 4K/30Hz@30bit, 4:2:2
 - 4K/60Hz@24bit, 4:2:0
- Maximum Distance: 1080P - 230 ft (70M), 4K - 130ft(40M)
- Compatible with 3D signals

AUDIO

- Audio transmission full pass-through
- LPCM 7.1 192KHz, Dolby TrueHD, DTS-HD MA

POWER

- Wall Transformer: 5VDC/ 2A, 2.5 mm connector
- TX Max current: 600mA Power: 0.8-3 W
- RX Max current: 12000mA Power: 1-6 W

I/O PORTS

- Transmitter/Receiver HDMI type A
- RJ45 Data Connector
- 2.5mm X 5.5mm female connector Power jack
- 3.5mm Stereo female phone jack IR signal
- LED Indicators: Pwr On = Green, Link = Blue

RJ45 Define: Video Link (TIA/EIA-568-B)

- | | |
|---------------------------|--------------------------|
| 1. Orange-White: DATA 0 + | 5. Blue-White: DATA 2 - |
| 2. Orange: DATA 0 - | 6. Green: DATA 1 - |
| 3. Green-White: DATA 1 + | 7. Brown-White: DATA 3 + |
| 4. Blue: DATA 2 + | 8. Brown: DATA 3 - |

IR

- Connector 3.5mm Phone Jack
- IR Carrier Frequency: 30 - 60Khz
- IR Angle: Transmitter ± 15°
- IR Angle: Receiver ± 55°
- IR Distance: 5m / Bi-directional

ACCESSORIES

- 2 Power wall adapters
- 1 IR Receiver
- 1 IR Transmitter
- Set of 4 Plastic Drywall Anchors
- Product Manual

MISCELLANEOUS

- Dimensions Transmitter/Receiver: (H) 1.09", (W) 1.95", (D) 3.50"
- Weight 0.476oz each
- Operating Temp & Humidity 0-55C, 95% Max Rel. Humidity
- Rugged (Industrial) Power Coated Steel Chassis

HDBaseT Distance Chart By Cable type:

| CAT.5e / CAT.6 | CAT.6a / CAT.7 | CAT.5e / CAT.6 | CAT.6a / CAT.7 |
|-----------------------------------|-----------------------------------|--|--|
| Range: 60m | Range: 70m | Range: 35m | Range: 70m |
| Pixel Clock Rate: ≤ 225MHz | Pixel Clock Rate: ≤ 225MHz | Pixel Clock Rate: > 225MHz | Pixel Clock Rate: > 225MHz |
| Video Data Rate: ≤ 5.3Gbps (HD) | Video Data Rate: ≤ 5.3Gbps (HD) | Video Data Rate: > 5.3Gbps (UHD) | Video Data Rate: > 5.3Gbps (HD) |
| Supported video:1080p 60Hz 36-bit | Supported video:1080p 60Hz 36-bit | Supported video:1080p 60Hz 48-bit, 1080p 60Hz 3D, 4K*2K 30Hz | Supported video:1080p 60Hz 48-bit, 1080p 60Hz 3D, 4K*2K 30Hz |

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
 1-800-767-6189
 sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

