



PD4861 D-Line Displays

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Professional-Grade

The D Line display series have a powerful Android OS and are designed specifically for digital signage that engages, informs, and entertains.



APPS

CE Labs partners with best-in-class software companies to transform our products into enterprise business solutions.



3 Year Warranty

All D-Line displays are built for professionals and come superior customer support and a standard with a 3 Year warranty.

PRODUCT OVERVIEW

CE Labs and Philips Professional Display Solutions have partnered to provide best-in-class 4K ultra high-definition commercial-grade display solutions for enterprise applications. The 4K D Line Commercial Display Series is specifically designed for digital signage applications that require 24-hour operation. With features like integrated Wi-Fi, 2 x 10W RMS built-in speakers, 500 cd/m² brightness, and a 178-degree enhanced view angle, the D Series truly stands out in its class. Powered by the Android operating system The D Line commercial display offers vibrant 4K content that engages, informs, and entertains.

When combined with a CE Labs media player preloaded with CESync™, our intuitive out-of-the-box experience makes connecting your D Line display quick and easy. Using one of our Android partner apps, you can create a self-service kiosk, a queue management system, or eye-catching digital signage.

FEATURES

Powerful Android Operating System (SoC)

500 cd/m² Brightness for enhanced viewing

Industry leading efficiency with Energy saving Smart Power

SPECIFICATIONS

MODEL: PD4861

Picture/Display

- Diagonal screen size: 85.6 inch / 217.4 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60Hz
- Brightness: 500 cd/m²
- Contrast ratio (typical): 1200:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing angle (H / V): 178 / 178 degree
- Pixel pitch: 0.4935 x 0.4935 mm
- Display colors: 1.07 Billion
- Panel technology: IPS
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, 3D MA deinterlacing, Dynamic contrast enhancement, Motion compens. deinterlacing, Progressive scan
- Clinical image: D-Image preset (dicom part 14 compatible)
- Operating system: Android 8.0

Supported Display Resolution

• Computer formats

Resolution	Refresh rate
3840 x 2160	30, 60Hz
1920 x 1080	60Hz
1680 x 1050	60Hz
1600 x 900	60Hz
1440 x 900	60Hz
1280 x 1024	60Hz
1280 x 720	60Hz
1024 x 768	60Hz
800 x 600	60Hz
640 x 480	60Hz

• Video formats

Resolution	Refresh rate
2160p	24, 30, 60Hz
1080p	50, 60Hz
1080i	50, 60Hz
720p	50, 60Hz
576p	50Hz
576i	50Hz
480p	60Hz
480i	60Hz

Connectivity

- Video input: Display Port1.2 (x1), DVI-I (x1), HDMI 2.0 (x3), USB 2.0 (x2)
- Video output: DisplayPort 1.2 (x1), HDMI 2.0 (x1)
- Audio input: 3.5 mm jack
- Audio output: 3.5mm jack
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack
- Other connections: OPS

Convenience

- Placement: Landscape (24/7), Portrait (24/7)
- Tiled Matrix: Up to 15 x 15
- Keyboard control: Hidden, Lockable
- Signal loop through: IR Loophrough, DisplayPort, HDMI, RS232
- Network controllable: RS232
- Energy saving functions: Smart Power
- Screen saving functions: Pixel Shift, Low Bright

Dimensions

- Set dimensions (W x H x D): 1929.0 x 1100 x 69.5(D@Wall mount) /91.8(D@Handle) mm
- Set dimensions in inch (W x H x D): 75.94 x 43.31 x 2.74(D@Wall mount) / 3.61(D@Handle) inch
- Bezel width: 15.5 mm (Even bezel)
- Product weight (lb): 111.11 lb
- Product weight: 50.4 kg
- VESA Mount: 600(H)x400(V) mm, M8

Operating conditions

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Altitude: 0 ~ 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20 - 80% RH (No condensation)
- Humidity range (storage) [RH]: 5 - 95% RH (No condensation)

Power

- Standby power consumption: <0.5 W
- Mains power: 100 ~ 240 VAC, 50 ~ 60Hz
- Consumption (Typical): TBD W
- Consumption (Max): TBD
- Energy Label Class: G

Sound

- Built-in speakers: 2 x 10W RMS

Accessories

- Included accessories: Quick start guide, RS232 cable, AC Power Cord, IR sensor cable (1.8M), Remote Control & AAA Batteries
- Included Accessories: RS232 daisy-chain cable, Philips logo (x1), AC Switch Cover, USB Cover (x1), Screws

Multimedia Applications

- USB Playback Audio: AAC, HEAAC, MPEG
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Video: MPEG, H.263, H.264, H.265, VP8

Miscellaneous

- Warranty: 3 year warranty
- On-Screen Display Languages: Simplified Chinese, Traditional Chinese, English, French, German, Italian, Polish, Russian, Spanish, Turkish, Japanese, Arabic
- Regulatory approvals: CE, RoHS, BSMI, CB, CCC, CU, EMF, EnergyStar 8.0, ETL, FCC, Class A, PSB, VCCI

Internal Player

- CPU: 2 x A53 + 2 x A73
- GPU: ARM Mali G51
- Memory: 3GB DDR
- Storage: 32 GB eMMc

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States

1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

