



TD4150 Touch Displays

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Professional-Grade

CE Labs Touch displays, with their durable construction and ultra-sleek design, are ideal for creating an interactive experience that engages and entertains.



APPS

CE Labs Touch Displays are compatible with hundreds of Android apps. With endless possibilities we have a business solution right for you.



3 Year Warranty

Our Touch displays are built for professionals and come superior customer support and a standard with a 3 Year warranty.

PRODUCT OVERVIEW

The CE Labs all-in-one Touch Display series is one of the most versatile product lines on the market. The TD Series, powered by Android, outperforms the competition with a best-in-class 10-point multi-touch IPS display, integrated Wi-Fi, and optional Power-over-Ethernet (POE). The TD product line is available in black or white and a variety of sizes. With their compact form factor and sleek design, CE Labs touchscreen displays provide a cost-effective, commercial-grade solution ideal for professional applications that require reliable 18/7 performance.

With CESync™, our intuitive out-of-the-box experience makes connecting your Touch display quick and easy. With the addition of one of our many SaaS partner apps, a CE Labs touch display is ideal for retail point of purchase displays, interactive kiosks, corporate, and hospitality environments.

FEATURES

24/7 Performance

Responsive Multi-Point touchscreen

Gigabit ethernet and Wi-Fi for superior connectivity

SPECIFICATIONS

MODEL: TD4150

DISPLAY

Panel: Full HD 15.6" LCD panel
Resolution: 1920*1080
Touch screen: 10-Point capacitive touch
Active area: 344.16mm(H) x 193.59mm(V)
Viewing angle: 85/85/85/85(L/R/U/D)
Contrast Ratio: 700:1
Brightness: 250 cd/m²
Aspect Ratio: 16x9
Operation Hours: 18/7

SYSTEM

CPU: Hex core Cortex
RAM: 2GB
Internal Memory: 16GB
Operating System: Android 9
CESync Software

MULTIMEDIA APPLICATIONS

Video formats: MPEG-1/MPEG-2/MPEG-4/H.263/H.264/VC1/RV
Audio formats: MP3/WMA/AAC
Picture formats: JPEG, PNG, Webp

DIMENSIONS

Dimensions: w15.28" x h9.65" x d1.06" / (388mm x 245mm x 27mm)
Product weight: 2.87lbs / 1.3kg

ACCESSORIES

Power adapter: 100-240Vac 50/60Hz, 12Vdc/1500mA. EL VI, UL
Quick start guide

NETWORK

Ethernet: 100M/1000M
Wifi: 802.11b/g/n/ac, 2.4GHz + 5GHz
Bluetooth: 4.0
Cellular: 3G USB dongle ext.

I/O PORTS

Power Jack: DC power input 12V/1.5A
HDMI: 2.0 Output
USB: Host 2.0. USB for serial, Mini USB OTG
Card slot: SD [supports up to 32GB]
RJ45: 100M/1000M Ethernet
Earphone: 3.5mm earphone
Power button
Recovery button

OPERATING CONDITIONS

Temperature range (operation): 0-40°
Temperature range (storage): 20 - 60°
MTBF: 50,000 hour(s)
Humidity range (operation) [RH]: 20 ~ 80% RH (No condensation)
Humidity range (storage)[RH]: 5 ~ 95% RH (No condensation)

MISCELLANEOUS

Wall mounting bracket: 100mm*100mm
Multi-language support
Optional camera: 2MP

WARRANTY: *3 year warranty, parts and labor.



Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

