



UHX70M 4K HDMI Extender

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs extenders are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The UHX70M is a commercial-grade Ultra-High Definition HDMI Extender kit. The UHX70M supports 4K/60 @70M. With an ultra-compact and rugged chassis the UHX70M is ideal for professional environments that require 24/7 performance.

The CE Pro-link™ of HDMI extender kits are the latest generation of reliable HDMI extenders for HD/4K/UHD AV signals. The CE Pro-link™ series includes HD and UHD models with a variety of powering and extension distance options. Perfect for AV professionals that demand the most cost effective and installation-friendly features.

FEATURES

Compact Design and rugged steel chassis

Most cost Effective HDMI Extension solution

75% lower power consumption

SPECIFICATIONS

MODEL: UHX70M

FEATURES

- Extends HDMI signal over one CAT6/6a/7 cable - 4K UHD/60Hz
- Extends IR signal over one CAT 6/6a/7 cable
- Transmission range up to 70M by CAT 6/6a/7
- Do NOT use STP cable
- Support 4K*2K @60Hz at 70M, 1080p@60Hz@48bit at 100m
- Bidirectional IR control
- Two way IR selectable
- HDMI 2.0 and HDCP 2.2/1.4 and DVI Compliant
- RoHS, CE, FCC Compliant
- Cat Cable 6/6a/7 Distance: Min. 10 ft (3M) - Max. 230 ft (70M)
- HDMI Cable Type A Distance: Min. 2 ft - Max. 16 ft, Type A
- 18 Gbps (6 Gbps per color)
- Transmitter has loop out for local display

VIDEO

- HDMI 2.0
- HDCP 2.2/1.4 & DVI compliant
- Maximum Resolution: 4K/60Hz 4:4:4 | 1080p/60Hz@48 bit
- Max. Distance: 4096x2160@60Hz 4:4:4 230ft(70M) | 1080p/60Hz 12bit: 330ft(100M) | CAT 6/6a/7 4096x2160 @60Hz 4:4:4 330ft(100M) | Zero video latency

AUDIO

- Audio support up to LPCM7.1, Dolby TrueHD, DTS-HD MA
- Audio transmission full pass-through

RJ45 Define: Video Link (TIA/EIA-568-B)

- | | |
|---------------------------|--------------------------|
| 1. Orange-White: DATA 0 + | 5. Blue-White: DATA 2 - |
| 2. Orange: DATA 0 - | 6. Green: DATA 1 - |
| 3. Green-White: DATA 1 + | 7. Brown-White: DATA 3 + |
| 4. Blue: DATA 2 + | 8. Brown: DATA 3 - |

POWER

- Wall transformer: 5VDC/ 2A, 2.5 mm connector
- TX Max current: 420mA Power: 0.263-1 Amp
- RX Max current: 800mA Power: 1-4 W or 0.324-1.6 Amp

I/O PORTS

- Transmitter/Receiver HDMI type A
- RJ45 Data Connector
- 2.5mm X 5.5mm female connector Power jack
- 3.5mm Stereo female phone jack IR signal
- LED Indicators: Pwr On, Blue

IR

- Connector 3.5mm
- IR Carrier Frequency: 30 - 60Khz
- IR Angle: Transmitter ± 10°
- IR Angle: Receiver ± 55°
- IR Distance: 5m / Bi-directional

ACCESSORIES

- 1 IR Transmitter
- 1 IR Receiver
- 2 Power wall adapters
- 4 Mounting Ears w/Screws
- Product Manual

MISCELLANEOUS

- Transmitter Dims.: (H) 0.8", (W) 4.0", (D) 4.2" | Weight 10oz.
- Receiver Dims.: (H) 0.8", (W) 4.0", (D) 4.2" | Weight 10oz.
- Operating Temp & Humidity 0-55C, 95% Max Rel. Humidity
- Rugged (Industrial) Powder Coated Steel Chassis

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

