



UHX120M 4K HDMI Extender

Commercial-Grade



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs extenders are perfect for any project that requires 24/7 performance.



CE PROLink™

CE Labs PROLink™ Series creates a fully connected PROAV ecosystem. Easily connect, control, and manage your entire network.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The UHX120M is a commercial-grade Ultra-High Definition HDBaseT HDMI Extender kit. The UHX120M supports 4K/60/4:4:4 @120M. With an ultra-compact and rugged chassis the UHX100M is ideal for professional environments that require 24/7 performance.

The CE Pro-link™ of HDMI extender kits are the latest generation of reliable HDBaseT extenders for HD/4K/UHD AV signals. The CE Pro-link™ series includes HD and UHD models with a variety of powering and extension distance options. Perfect for AV professionals that demand the most cost effective and installation-friendly features.

FEATURES

Compact Design and rugged steel chassis

Most cost Effective HDBaseT solution

POC remote power

SPECIFICATIONS

MODEL: UHX120M

FEATURES

- Uses HDBaseT technology
- Extends HDMI signal over one CAT5e/6/6a/7 cable - 4K UHD/60Hz with 4:4:4
- Extends IR and RS232 signal over one CAT5e/6/6a/7 cable
- Transmission range up to 120M by CAT 6/6a/7
- Do NOT use STP cable
- Support 1080p@60Hz@48bit & 150m 4K*2K @60Hz @ 120M
- Built in IR control bidirectional
- Two way IR selectable
- HDMI 2.0 and HDCP 2.2/1.4 and DVI Compliant
- RoHs, CE, FCC Compliant
- Cat Cable 5e/6/6a/7 Distance: Min. 10 ft (3M) - Max. 394 ft (120M)
- HDMI Cable Type A Distance: Min. 2 ft - Max. 16 ft, Type A
- 18 Gbps (6 Gbps per color)
- Transmitter has loop out for local display

VIDEO

- HDMI 2.0
- HDCP 2.2/1.4 & DVI compliant
- Maximum Resolution: 1080p/60Hz@48 bit | 4K/60Hz 4:4:4
- Max. Distance: 1080p/60Hz 12bit: 492ft (150M) | CAT 5e/6 4096x2160@60Hz 4:4:4(90M) | CAT6a/7 4096x2160 @60Hz 4:4:4 394ft(120M) | Zero video latency

AUDIO

- Audio support up to LPCM7.1, Dolby TrueHD, DTS-HD MA, Dolby Digital
- Audio transmission full pass-through

POWER

- Wall transformer: 24VDC/ 1A, 2.1 mm connector, lock ring
- TX Max power: 5.5W
- RX Max power: 4.5W

I/O PORTS

- Transmitter/Receiver HDMI type A
- RJ45 Data Connector
- 2.1mm X 5.5mm female connector Power jack with lock ring
- 3.5mm Stereo female phone jack IR signal
- LED Indicators: Pwr On, Link, Video
- RS-232 jack, 3-PIN Pheonix

IR

- Connector 3.5mm
- IR Carrier Frequency: 30 – 60Khz
- IR Angle: Transmitter ± 10°
- IR Angle: Receiver ± 55°
- IR Distance: 5m / Bi-directional

RJ45 Define: Video Link (TIA/EIA-568-B)

- | | |
|---------------------------|--------------------------|
| 1. Orange-White: DATA 0 + | 5. Blue-White: DATA 2 - |
| 2. Orange: DATA 0 - | 6. Green: DATA 1 - |
| 3. Green-White: DATA 1 + | 7. Brown-White: DATA 3 + |
| 4. Blue: DATA 2 + | 8. Brown: DATA 3 - |

ACCESSORIES

- 1 IR Transmitter, 1 IR Receiver
- 1 Power wall adapter
- 2 Mounting ears
- 2 3-PIN Pheonix connectors
- Product Manual

MISCELLANEOUS

- Transmitter Dims.: (H) 0.75", (W) 5.5W", (D) 2.6" | Weight 8oz.
- Receiver Dims.: (H) 0.75", (W) 5.5", (D) 2.6" | Weight 9oz.
- Operating Temp & Humidity 0-40°C, 95% Max Rel. Humidity
- Rugged (Industrial) Powder Coated Steel Chassis
- RS232 3-PIN Pheonix jack

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

