



CE460 4K Pro Media Player

Dolby Vision



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs media players are perfect for any project that requires 24/7 performance.



APPS

CE Labs' hardware platform supports hundreds of apps. With endless possibilities we have a business solution right for you.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The CE460 is a world-class UHD/HDR/4K media player, specifically engineered for professional retail applications. Powered by a robust 4K Quad Core CPU, the CE460 delivers true commercial-grade performance, effortlessly supporting dual decoding of two H.265/H.264 4K60 videos simultaneously. With the inclusion of Dolby Vision technology, the CE460 produces extraordinary visuals with unparalleled brightness, deeper contrasts, and stunningly vivid colors, ensuring content that stands out in any retail environment.

Packed with industry-leading features and exceptional reliability, the CE460 is a true enterprise-level powerhouse. Its advanced I/O package includes Gigabit Ethernet, POE, GPIO, ATSC/QAM Tuner, RS-232, dual Wi-Fi, and 64GB internal memory. Paired with best-in-class CMS software, the CE460 with Dolby Vision technology delivers captivating, informative, and entertaining content that elevates customer engagement and drives brand impact.

FEATURES

Ultra 4K Digital Signage playback enhanced by Dolby Vision, delivering exceptional brightness, deeper contrast, and vivid colors, all powered by our most advanced quad-core processor.

Large capacity 64GB Internal storage. Expandable micro-SD for up to 1TB of additional storage.

Ultra-fast Gigabit ethernet with optional PoE. Superior connectivity with Dual Band Antennas for best-in-class Wi-Fi support.

SPECIFICATIONS

MODEL: CE460

FEATURES

- 4K UHD HDMI 2.1 Output
- Quad Core Processor w/Dual GPU
- 4GB DDR4 RAM
- 64GB Internal Memory
- Gigabit Ethernet
- Internal Wi-Fi 802.11 a/b/g/n/ac with Dual Antennas
- Real Time Clock
- HTML5 Full Support
- Dolby Vision, HDR 10, HLG
- CESync Software
- Stereo Audio DAC
- Commercial-Grade for Optimized 24/7 play operation
- Connect interactive devices (USB/GPIO/RS-232)
- IP Streaming: play streaming media
- Live Feeds: Live data, Live Text, MRSS, Twitter, Flickr, etc.
- Mosaic Mode: multiple video zones
- Supports Custom Interactive Kiosks Applications

VIDEO / PICTURE CODEC

- VP9 Profile-2 up to 4Kx2K@60fps
- H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps
- AVS2-P2 Profile up to 4Kx2K@60fps
- H.264 AVC HP@L5.1 up to 4Kx2K@30fps
- MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)
- WMV/VC-1 SP/MP/AP up to 1080P@60fps
- MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)
- MPEG-1 MP/HL up to 1080P@60fps (ISO-11172)
- RealVideo 8/9/10 up to 1080P@60fps
- 8K webm VP9 @30fps
- Multiple language and multiple format sub-title video support
- Image Formats: TIFF, JPEG, GIF, PNG, WEBVTT, RokuBif, WebP

VIDEO FORMATS

- MP4 (mp4, m4a, m4v, f4v, f4a, m4b, m4r, f4b, mov)
- MOV, WMV, WEBM, MKV, FLV, AVI, HDV, MXF, AVCHD, LXF, VOB
- 3GP (3gp, 3gp2, 3g2, 3gpp, 3gpp2), OGG (ogg, oga, ogv, ogx)
- MPEG-TS, MPEG-2 PS, MPEG-2 TS
- MPEG, MP2, MPEG, MPE, MPV

AUDIO FORMATS

- MP3, AAC, AC3, EAC3, WMA, RM, FLAC, OGG, PCM, ATMOS(passthrough)
- Programmable with 7.1/5.1 down-mixing
- SPDIF supports 192KHz 16/24/32bit stereo

I/O PORTS

- HDMI 2.1 Output Transmitter
- Gigabit Ethernet
- 12 Pin GPIO Jack, Phoenix style port with 8 channels
- Locking Coaxial Power Jack, 12Vdc
- External Micro SD Socket (SDHC or SDXC)
- Dual SMA Jacks for Wi-Fi Antennas
- RS-232, 3.5mm Jack
- TOSLINK – R/L Audio, 3.5mm Jack
- USB 3.0 Type
- USB 2.0 Type
- External Reset Jack, 2.5mm
- Internal IR Receiver
- LED Indicators for Power, Status, LAN

NETWORK

- Integrated 802.3 10/100/1000M Ethernet MAC with RGMII interface
- IP, TCP, UDP, ICMP, ARP, DHCP, HTTP, RTP, RTSP, NTP, DNS

ACCESSORIES

- Power Adapter, 100-240Vac 50/60Hz, 12Vdc/1500mA, EL VI, UL
- IR Remote w/2 AAA Batteries
- 2 Wi-Fi Antennas
- HDMI 2.0 High Speed Cable
- Quick Start Guide
- GPIO Mating Connector, 12 Pin Phoenix Style

MISCELLANEOUS

- Dimensions (H) 0.77", (W) 7.7", (D) 4.0" / 20 x 195 x 104 mm
- Weight 0.9 lbs. / 0.4 kg
- Operating Temp & Humidity 0-40C, 80% Max Rel. Humidity
- Includes Rubber Standoff Feet
- Integrated Mounting Brackets
- Low Profile Design
- Rugged (Industrial) Cast Aluminum Chassis

OPTIONAL FEATURES (Add-On)

- PoE+ Module, Internal
- Tuner – ATSC 1.0 / QAM
- GPIO External Wire Harness / Illuminated Buttons
- USB Button Control Pad
- MicroSDXC Class 10 Cards (Various Capacities)

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

