



CE460 4K Pro Media Player

Dolby Vision



One Platform, Endless Possibilities

An Ecosystem of products specifically designed for professionals.



Commercial-Grade

With durable construction and ultra-sleek design, CE Labs media players are perfect for any project that requires 24/7 performance.



APPS

CE Labs' hardware platform supports hundreds of apps. With endless possibilities we have a business solution right for you.



3 Year Warranty

CE Labs products are built for professionals. All products come with a 3-year warranty and superior customer support.

PRODUCT OVERVIEW

The CE460 is a world-class UHD/HDR/4K media player, specifically engineered for professional retail applications. Powered by a robust 4K Quad Core CPU, the CE460 delivers true commercial-grade performance, effortlessly supporting dual decoding of two H.265/H.264 4K60 videos simultaneously. With the inclusion of Dolby Vision technology, the CE460 produces extraordinary visuals with unparalleled brightness, deeper contrasts, and stunningly vivid colors, ensuring content that stands out in any retail environment.

Packed with industry-leading features and exceptional reliability, the CE460 is a true enterprise-level powerhouse. Its advanced I/O package includes Gigabit Ethernet, POE, GPIO, ATSC/QAM Tuner, RS-232, dual Wi-Fi, and 64GB internal memory. Paired with best-in-class CMS software, the CE460 with Dolby Vision technology delivers captivating, informative, and entertaining content that elevates customer engagement and drives brand impact.

FEATURES

Ultra 4K Digital Signage playback enhanced by Dolby Vision, delivering exceptional brightness, deeper contrast, and vivid colors, all powered by our most advanced quad-core processor.

Large capacity 64GB Internal storage. Expandable micro-SD for up to 1TB of additional storage.

Ultra-fast Gigabit ethernet with optional PoE. Superior connectivity with Dual Band Antennas for best-in-class Wi-Fi support.

SPECIFICATIONS

MODEL: CE460

FEATURES

4K UHD HDMI 2.1 Output
Quad Core Processor w/Dual GPU
4GB DDR4 RAM
64GB Internal Memory
Gigabit Ethernet
Internal Wi-Fi 802.11 a/b/g/n/ac with Dual Antennas
Real Time Clock
HTML5 Full Support
Dolby Vision, HDR 10, HLG
CESync Software
Stereo Audio DAC
Commercial-Grade for Optimized 24/7 play operation
Connect interactive devices (USB/GPIO/RS-232)
IP Streaming: play streaming media
Live Feeds: Live data, Live Text, MRSS, Twitter, Flickr, etc.
Mosaic Mode: multiple video zones
Supports Custom Interactive Kiosks Applications

VIDEO / PICTURE CODEC

VP9 Profile-2 up to 4Kx2K@60fps
H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps
AVS2-P2 Profile up to 4Kx2K@60fps
H.264 AVC HP@L5.1 up to 4Kx2K@30fps
MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)
WMV/VC-1 SP/MP/AP up to 1080P@60fps
MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)
MPEG-1 MP/HL up to 1080P@60fps (ISO-11172)
RealVideo 8/9/10 up to 1080P@60fps
8K webm VP9 @30fps
Multiple language and multiple format sub-title video support
Image Formats: TIFF, JPEG, GIF, PNG, WEBVTT, RokuBif, WebP

VIDEO FORMATS

MP4 (mp4, m4a, m4v, f4v, f4a, m4b, m4r, f4b, mov)
MOV, WMV, WEBM, MKV, FLV, AVI, HDV, MXF, AVCHD, LXF, VOB
3GP (3gp, 3gp2, 3g2, 3gpp, 3gpp2), OGG (ogg, oga, ogv, ogx)
MPEG-TS, MPEG-2 PS, MPEG-2 TS
MPG, MP2, MPEG, MPE, MPV

AUDIO FORMATS

MP3, AAC, AC3, EAC3, WMA, RM, FLAC, OGG, PCM,
Atmos(passthrough)
Programmable with 7.1/5.1 down-mixing
SPDIF supports 192KHz 16/24/32bit stereo

I/O PORTS

HDMI 2.1 Output Transmitter
Gigabit Ethernet
12 Pin GPIO Jack, Phoenix style port with 8 channels
Locking Coaxial Power Jack, 12Vdc
External Micro SD Socket (SDHC or SDXC)
Dual SMA Jacks for Wi-Fi Antennas
RS-232, 3.5mm Jack
TOSLINK – R/L Audio, 3.5mm Jack
USB 3.0 Type
USB 2.0 Type
External Reset Jack, 2.5mm
Internal IR Receiver
LED Indicators for Power, Status, LAN

NETWORK

Integrated 802.3 10/100/1000M Ethernet MAC with RGMII interface
IP, TCP, UDP, ICMP, ARP, DHCP, HTTP, RTP, RTSP, NTP, DNS

ACCESSORIES

Power Adapter, 100-240Vac 50/60Hz, 12Vdc/1500mA, EL VI, UL
IR Remote w/2 AAA Batteries
2 Wi-Fi Antennas
HDMI 2.0 High Speed Cable
Quick Start Guide
GPIO Mating Connector, 12 Pin Phoenix Style

MISCELLANEOUS

Dimensions (H) 0.77", (W) 7.7", (D) 4.0" / 20 x 195 x 104 mm
Weight 0.9 lbs. / 0.4 kg
Operating Temp & Humidity 0-40C, 80% Max Rel. Humidity
Includes Rubber Standoff Feet
Integrated Mounting Brackets
Low Profile Design
Rugged (Industrial) Cast Aluminum Chassis

OPTIONAL FEATURES (Add-On)

PoE+ Module, Internal
Tuner – ATSC 1.0 / QAM
GPIO External Wire Harness / Illuminated Buttons
USB Button Control Pad
MicroSDXC Class 10 Cards (Various Capacities)

WARRANTY: *3 year warranty, parts and labor.

Learn more about CE Labs at www.celabs.com.

United States
1-800-767-6189
sales@celabs.com

CE Labs, LLC reserves the right to change or update without notice. CE Labs, the CE Labs logo and CESync are registered trademarks of CE Labs, LLC. All other trademarks are the property of their respective owner. 2021 CE Labs, LLC. All rights reserved.

